### Professional Tool & Equipment News

### The Independent Tool Authority

## 2019 POWERTOOL SPEC GUIDE

A COMPREHENSIVE GUIDE TO HELP YOU CHOOSE THE RIGHT CORDLESS TOOL OR AIR TOOL FOR YOUR NEEDS IN ASSOCIATION WITH THE FOLLOWING PTEN-AFFILIATED PUBLICATIONS:







#### The W7152 from Ingersoll Rand®

is the most powerful  $\frac{1}{2}$  cordless impact wrench in its class. Delivering 1500 ft-lbs of nut-busting torque and utilizing the IQ<sup>V</sup> Intelligent Control System, the W7152 can go from MAX torque to "hand tight" in no time.

#### **REAL TOOLS FOR REAL WORK.**



W7152-K22



Enter 100 at "e-inquiry" on VehicleServicePros.com

Learn more at www.irtools.com/w7152



## **Power tool comparison**

Determine the right cordless and air tools for your shop based on function, features and size.

ower tools are the workhorses of any shop. Whether you are looking to upgrade an existing tool, or try something new, it pays to research and compare the latest models available. We've compiled a guide of some of the newest and most popular power tools to help you in this pursuit. The criteria in this guide include torque requirements, available space, tool category and battery size. See the specs side-by-side, and consider which model will best stand up to frequent, repeated use and certain vehicle-specific tasks.

For the 2018 guide, we focused on the cordless and air tool configurations most commonly used in automotive repair — impact wrenches and ratchets — in the most common voltages and drive sizes. Each cordless tool is broken out by voltage to illustrate like-comparisons. Cordless impact wrenches are categorized by 12V/14V and 18V/20V, and impact ratchets 12V/14V of battery power. Voltage is important to note as battery dictates both the run-time and size of a cordless tool. Although batteries add weight, today's Li-ion cells have made great strides in the last few years to enhance run-time and performance for frequent and prolonged use. Take a look and consider the right balance of weight, power and run-time for each featured tool.

We've also incorporated air tools into this year's guide. Air tools remain a staple in many shops, as they can help to speed up work and help to remove tough fasteners, and loosen stubborn nuts and bolts. The air tools in this guide are broken out by drive size: 1/2", 3/4", 3/8" and 1" for impact wrenches, and 3/8" and 1/2" for ratchets.

Whether you are looking to purchase a cordless tool or an air tool, consider the application the tool will be used for most often. Will you need to get into an extra-snug area? If so, a mini drive impact wrench might be your best bet.

Also consider power-to-size and power-toweight ratios. As drive size and torque ability increase, so does overall tool size and weight. Smaller, low-torque 1/4" and 3/8" impact wrenches are popular choices for light duty vehicle work where space is limited, while high torque settings and increased size and weight are ideal for heavy duty applications.

These days it seems there is a power tool available for just about every job, preference and price range. In fact, the hardest part may be deciding which one will be the best fit for your toolbox.

Note: On the following spec guide pages, blank fields indicate information not provided by manufacturer; other fields indicate function not available on tool.

\*Cover photo provided by Ingersoll Rand



## MPACT WRENCH - 12V/14V

COMPANY NAME	Makita	Matco Tools	Snap-on Tools	
PRODUCT NAME	12V max CXT Lithium-Ion Cordless 3/8" Impact Wrench Kit	12V Cordless Infinium 1/4" Impact Wrench Kit	14.4 Volt 3/8" Square Drive Impact	
Product model number:	WT02R1	MCL1214IWK	CT761A	-
Price				
\$101-250	Battery included			
\$251-500		Battery included	Battery included	
\$501-\$1,000				
Over \$1,000				
Manufacturing Specs				
Maximum rpm	2,600 rpm		2,500 rpm	
Working rpm			0-2,500 rpm	
Maximum tightening torque	103 ft-lbs	60 ft-lbs	120 ft-lbs	
Breakaway/nut-busting torque		100 ft-lbs	140 ft-lbs	
Sound level			94.5 dBA	
Drive size	3/8"	1/4"	3/8"	
Spindle size	,	,		
Interchangeable left- or right-hand operation	•		•	
Anti-vibration		•		
Tool weight (with battery)	2.3 lbs	3 lbs	2.5 lbs	
Overall tool length	6-3/8"	9"	6.3"	-
Product Features	00,0	J	0.0	
Battery type	Li-ion	Li-ion	Li-ion	
Battery voltage	12V	12V	14.4V	
Battery pack capacity	2.0Ah	2.0 Ah	2.0 Ah	-
Time to full battery charge	2.011	Lioni	55 min	
Time unit lasts before recharge			Varies by application	
Motor type	Brushless		Brushed	
Motor amperage			30-35A	
Adjustable torque setting? If so, how many?				
Built-in work light	•	•	•	
Variable speed trigger	•	•	•	
Length of manufacturer warranty	3 years	2 years	1 year	
Batteries and Accessories		<b>1</b> • • •		
Battery and charger included	•	•	•	
Bare tool available	•	•	•	
Additional batteries available for purchase separately	•	•	•	<u> </u>
Battery compatible with other products	•	-	-	
Includes the following accessories:	2.0 Ah battery, charger, bag	Case, charger		-
Other accessories available for purchase separately:	4.0 Ah battery, charger, Impact GOLD 3/8" SAE Socket Set, LED Flashlight, Adjustable Beam LED Flashlight		3/8" drive sockets	
Comes in a carrying case	•	•	•	
If Yes to above, blow molded case or canvas bag?	Canvas bag	Canvas bag	Canvas bag	
Application (mark all that apply)				
Small interior fasteners	•	•	•	
Body panel bolts	•	•	•	
Shroud covers	•	•	•	
Suspension bolts	•			
Tire service/lug nuts	•			
Brake jobs	•	•		
Engine	•	•	•	
Interior/exterior work	-	•	•	
Under dash	•	•		
Underhood		•		
Tractor/trailer repair	•		•	
Other				
Most unique feature	Makita-built brushless motor delivers 103 ft-lbs of max torque	One of the smallest tools on the market, according to the company; provides up to 60 ft-lbs of max torque	Powerful 120 ft-lbs output, hard hitting compact design, variable speed toggle trigger	



N
S
Ċ
Δ
Ξ
0
Q
m
5
2
~
5

ACDelco	Bosch	Chicago Pneumatic Tools	Ingersoll Rand	Milwaukee Tool
Li-ion 12V 3/8" Impact Wrench	12V Max Brushless Impact Wrench	Cordless 1/4" Impact Driver	IQV12 Series 3/8" 12V Square with Ring Impact Wrench	M12 FUEL 3/8" Stubby Impact Wrench with Friction Ring Kit
ARI12104	PS82BN	CP8818	W1130	2554-22
11112201	1002511	0.0010		
Battery included	Bare tool		Bare tool	Battery included
		Battery included	Battery included	
2,800 rpm	2,600 rpm	2,000 mm	2,700 rpm	0-3,200 rpm
2,000 10111		2,000 rpm		
90 ft-lbs	2,600 rpm 1,020 ft-lbs	85 ft-lbs	0-2,700 rpm 75 ft-lbs	0-3,200 rpm 250 ft-lbs
50 10-105	1,020 ft-lbs	05 10-105	100 ft-lbs	250 ft-lbs
	1,020 10-05	86.5 dBA	82 dBA	96.6 dBA
3/8"	3/8"	1/4"	3/8"	3/8"
5/0	5/0	1/ 7	3/8"	5/0
•	•	•	•	•
-		•		
1.98 lbs	1.6 lbs (bare tool)	2.4 lbs	2 lbs	2.92 lbs
6 1/4"	5.5"	6.3"	5"	4.8"
<i></i> , .			-	
Li-ion	Li-ion	Li-ion	Li-ion	Li-ion
12V	12V	12V	12V	12V
2.0 Ah		1.5 Ah	2.0 Ah	4.0 Ah
	< 60 min	90 min	75 min	40 min
	Varies by application	Varies by application	Varies by application	
	Brushless		Brushed	Brushless
	2			4
•	•	•	•	•
• 1.uppr	• 2.veen	•	• 2 vaara	5 years tool, 3 years battery
1 year	3 years	5 years	3 years	5 years tool, 5 years battery
•	With kit	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
	•	2 batteries, charger		2 batteries, charger, case
	•	Battery, charger		Rubber overmold, sockets
	•	Dattery, charger		
	•	•		•
	Canvas bag	Blow molded case		Canvas bag
•	•	•	•	•
•	•	•	•	
•	•	•	•	
•	•	•	•	
	•	-	•	•
	•		•	•
•	•		•	•
•	•	•	•	•
•	•	•	٠	•
•	•	•	•	•
٠	•		•	•
Compact size, lightweight, powerful, safe ergonomic handle for all-day use	Compact and easy to use; two-stage power setting	Ultra compact for work in small and confined spaces	Dependable, durable, compact, lightweight and easy to use with comfortable ergonomic grip	Industry's first cordless stubby impact, according to the company. Access in tight spaces, power for most tasks

## MPACT WRENCH - 18V/20V

COMPANY NAME	ACDelco	Chicago Pneumatic Tools	Ingersoll Rand	Matco Tools	
PRODUCT NAME	Li-ion 20V Brushless 1/2" JUMBO	Cordless 1/2" Impact Wrench	IQV20 Series 1/2" 20V High	20V Cordless Infinum 1/2" Drive High	
Product model number:	Impact Wrench ARI2002	CP8849	Torque Impact Wrench W7152	Performance Impact Wrench Kit MCL2012HPIWK	-
Price	1112002		11102	WOLLOI ZITI TITI	
\$101-250					
\$251-500			Bare tool		
\$501-750			Battery included	Battery included	
\$751-1,000	Battery included		Battery included	Duttory monado	
0ver \$1,000	Buttory monant	Battery included	Duttory morace		
Manufacturing Specs					
Maximum rpm	1,700 rpm	1,800 rpm	1,900 rpm	1,650 rpm	
Working rpm			0-1,900 rpm		
Maximum tightening torque	738 ft-lbs	850 ft-lbs	1,000 ft-lbs	1,300 ft-lbs	
Breakaway/nut-busting torque	1,100 ft-lbs	1,400 ft-lbs	1,500 ft-lbs	1,300 ft-lbs	
Sound level		112.5 dBA	95.7 dBA		
Drive size	1/2"	1/2"	1/2"	1/2"	
Spindle size			1/2"		
Interchangeable left- or right-hand operation	•		•		
Anti-vibration	•	•			
Tool weight (with battery)	7.26 lbs	7.96 lbs	7.6 lbs	7.8 lbs	
Overall tool length	9.27"	9.9"	8.1"	11.4"	
Product Features					
Battery type	Li-ion	Li-ion	Li-ion	Li-ion	
Battery voltage	20V	20V	20V	20V	
Battery pack capacity	4.0 Ah	4.0 Ah - 6.0 Ah	3.0 Ah, 5.0 Ah	4.0 Ah	
Time to full battery charge		90 min	55 min, 85 min	60 min	
Time unit lasts before recharge		Varies by application	Varies by application		
Motor type	Brushless	Brushless	Brushless	4-pole	
Motor amperage		Bruomoso	Diddinoto	1 poro	
Adjustable torque setting? If so, how many?	3	5 (4 fwd, 1 rev)	4		
Built-in work light	5	•	•	•	
Variable speed trigger	•	•	•	•	
Length of manufacturer warranty	1 year	5 years	3 years	1.5 years	
Batteries and Accessories	1 )	o jealo	0 /00.0	110 youro	
Battery and charger included	•	•	•	•	
Bare tool available	•	•	•	•	-
Additional batteries available for purchase separately	•	•	•	•	
Battery compatible with other products	•	•	•	•	
Includes the following accessories:		2 batteries, charger, bag	-	-	
Includes are ronowing accessories.					
Other accessories available for purchase separately:				Universal charger	
Comes in a carrying case		•	•	•	
If Yes to above, blow molded case or canvas bag?		Canvas bag	Canvas bag	Blow molded case	
Application (mark all that apply)					
Small interior fasteners			•		
Body panel bolts			•		
Shroud covers			•		
Suspension bolts	•		•	•	
Tire service/lug nuts	•	•	•	•	
Brake jobs	•		•	•	
Engine	•		•	•	
Interior/exterior work			•		
Under dash			•		
Underhood	•		•	•	
Tractor/trailer repair	•		•	•	
Other	Agriculture, aircraft		_	_	
Viici					
Most unique feature	3 specific fastening modes, metal gearbox, jumbo high-efficiency impact mechanism	4 forward settings, slow mode, fast mode, automatic shut-off	Powerful cordless 1/2" tool with task light and four power modes for more control and more jobs	Powerful 4 pole motor generates 1,300 ft-lbs of breakaway torque	



	Puma Air		Milwaukee Tool	Mac Tools	Makita	Bosch	Hazet
	Brushless Impact Wrench		M18 FUEL 1/2" High Torque Impact Wrench with Friction Ring Kit	20V MAX* 3/8" Brushless Impact Wrench	18V LXT Li-ion Sub-Compact Brushless Cordless 3/8" Square Drive Impact Wrench Kit	The Freak	Mini Cordless Impact Wrench
	PTFL5041		2767-22	MCF891M1D1	XWT12RB	IDH182	9212M-1
		ш					
		N				Bare tool	
Г	Battery included		Battery included	Battery included	Battery included		Battery included
1	,	S		,			,
		H					
		C					
		A					
	1,800 rpm	D	1,000 rpm	0-900/1,950/2,800 rpm	2,400 rpm	2,800 rpm	2,500 rpm
			0-1,700 rpm			2,800 rpm	2,500 rpm
	740 ft-Ibs		1,400 ft-lbs	150 ft-lbs	130 ft-Ibs	1,650 ft-lbs	162.24 ft-lbs
	1,100 ft-lbs	-COM	1,400 ft-lbs	275 ft-lbs		1,650 ft-lbs	200 ft-lbs
		Q	92.1 dBA				99.6 dBA
	1/2"	Ġ	1/2"	3/8"	3/8"	1/2"	1/2"
		D					
		SL	٠	٠	•	٠	•
	7.3 lbs		7.5 lbs	1.94 lbs	2.7 lbs	2.4 lbs (bare tool)	3 lbs
	8.7"		8.39"	5.69"	5-5/8"	6.2"	5.35"
		MIN					
	Li-ion		Li-ion	Li-ion	Li-ion	Li-ion	Li-ion
	20V		18V	20V	18V	18V	18V
	4.0 Ah		5.0 Ah	2.0 Ah, 4.0 Ah	2.0 Ah	1.5 Ah - 8.0 Ah	2.0 Ah
Γ	80 min		60 min	60 min	25 min	< 60 min	35 min
						Varies by application	Varies by application
	Brushless		Brushless	Brushless	Brushless	Brushless	Brushless
							4.5A
	5		4	3			4 (3 fwd, 1 rev)
	•		•	٠	•	•	•
	•		•	•	•	•	
	1 year		5 years tool, 3 years battery	1 year	3 years	3 years	2 years
Γ	•		•	٠	•	With kit	•
	•		•	٠	•	•	•
	•		•	•	•	•	•
	•		•	٠	•	•	•
Γ			2 batteries, charger, case		2.0 Ah battery, charger, bag	Belt clip, four-bit set, strap	Battery, charger, bag
	•		protective rubber boot, sockets		5.0 Ah battery, 4.0 Ah battery, 6.0 Ah battery, Impact GOLD 3/8" SAE socket set, Impact GOLD 3/8" metric socket set	٠	2.0 Ah battery, 5.0 Ah batter
	•		٠		•	•	•
	Blow molded case		Blow molded case		Canvas bag	Canvas bag	Canvas bag
			•	•	•	•	•
			•	•	•	•	•
			•	•	•	•	•
			•	•	•	•	•
	•		•		•		•
			•	•	•	•	•
			•	•	•	•	•
			•	•	•	•	•
			•	•	•	•	
			•	•	•	•	•
	•		•		•	•	
	Five modes		The first complete replacement for pneumatic and corded impact wrenches, according to the company	BL spec brushless motor technology	Sub-compact is ideal for working in tight spaces and overhead applications	1/4" hex bit holder and 1/2" square drive on one tool	Very small head for tight working areas

## MPACT RATCHET - 12V/14V

COMPANY NAME	Matco Tools		ACDelco	
PRODUCT NAME	12V Cordless Infinum 3/8" Drive Ratchet Kit		Li-ion 12V Brushless 3/8" Square Ratchet Wrench	
Product model number:	MCL1238RK		ARW1210-3	
Price		ш		
Under \$100		N		
\$101-250				
\$251-500	Battery included	S	Battery included	
\$501-1,000			· · · · · · · · · · · · · · · · · · ·	
Over \$1,000		U.		
Manufacturing Specs				
Mini/sub-compact size			•	
Maximum rpm	180 rpm		190 rpm	
Working rpm	180 rpm		·	
Maximum tightening torque	55 ft-lbs	B-COMP	65 ft-lbs	1
Breakaway/nut-busting torque		<b>O</b>	65 ft-lbs	
Sound level				
Drive size	3/8"	5	3/8"	
Spindle size			,	
Interchangeable left- or right-hand operation		S	•	
Anti-vibration		ŇW	•	
Tool weight (with battery)	3.1 lbs		3.08 lbs	
Overall tool length	13"		12.28"	
Product Features				
Battery type	Li-ion		Li-ion	
Battery voltage	12V		12V	
Battery pack capacity	2.0 Ah		2.0 Ah	1
Time to full battery charge	60 min			
Time unit lasts before recharge				-
Motor type	4-pole		Brushless	
Motor amperage				
Adjustable torque setting? If so, how many?				
Built-in work light	•		•	
Variable speed trigger	•		•	
Length of manufacturer warranty	2 years		1 year	
Batteries and Accessories				
Battery and charger included	•		•	
Bare tool available	•		•	
Additional batteries available for purchase separately	•		•	-
Battery compatible with other products	•		•	
Includes the following accessories:	Battery, charger, bag			-
Other accessories available for purchase separately:				-
Comes in a carrying case?	•			
If Yes to above, blow molded case or canvas bag?	Canvas bag			
Application (mark all that apply)				
Small interior fasteners	•		•	
Body panel bolts	•	-	•	
Shroud covers	_		•	
Suspension bolts			•	
Tire service/lug nuts				
Brake jobs			•	
Engine	•		•	
Interior/exterior work	•		•	
Under dash	•		•	
Underhood	•		•	
Tractor/trailer repair			•	
Other				
Most unique feature	55 ft-lbs max torque with compact design measuring 13"; ideal combination of size and power in a 3/8" drive		Industry leading max torque on any 3/8" ratchet wrench, three anvil sizes available, according to the company	
	combination of size and power in a 3/8 drive		three any sizes available, according to the company	

### PTEN

Ingrassil Rand         Microsofie Tool         Statup on Data           19/12 Statuk         112/12 Statuk         12/12 Statuk         12/12 Advice           R120         257.22         CR7144           Bart tool         Bart tool         Bart tool				
Pitho     267-22     CliP14A       Bart tod     Battery included     Bettery included       Bart tod     Battery included     Bettery included       280 gm     0.700 gm     350 gm       280 gm     0.700 gm     350 gm       30 bets     55 feas     35 feas       30 bets     55 feas     35 feas       16 add     32 gm     144       1/4*     3/4*     1/4*       1/4*     3/4*     1/4*       1/4*     3/8*     2.2 bit       11*     11.84*     1.14*       11*     11.84*     1.14*       11/1*     122     1.14*       11*     1.12*     1.14*       120 bit     2.0 bit     2.0 bit       11*     1.12*     1.14*       120     1.20     1.4*       120     2.0 bit     2.0 bit       13     2.0 bit     2.0 bit       1400     1.1*     1.1*       120     1.4*     1.1*       13     2.0 bit     2.0 bit       1400     1.2*     1.4*       1401     1.1*     1.2*       1402     2.0 bit     2.0 bit       10     2.0 bit     0       11*     1.1* <td< th=""><th></th><th>-</th><th></th><th></th></td<>		-		
Bare tool         Buttery included         Buttery included           Battery included         Buttery included         Buttery included           •         •         •           260 rpm         6.200 rpm         5.80 rpm           6.900 rpm         6.200 rpm         5.80 rpm           76.080 rpm         6.20 rpm         6.200 rpm           76.080 rpm         6.20 rpm         6.20 rpm           76.080 rpm         6.20 rpm         6.20 rpm           78.08         2.2.04 rpm         7.47           1/4"         1/4"         1/4"           1/4"         1/4"         10.75"           14m         Lim         Lim           12W         1/4         10.75"           14m         Lim         Lim           12W         1/4         2.04           12W         1/4         2.04           12W         1/4         3.0 rpm           13west         Systemator         1/1" for socials           14west         1/1" for socials				
Baltey included         Baltey included           Baltey included         Baltey included           0         0           100 (nm)         0.200 (nm)           0 200 (nm)         0.200 (nm)           0 30 belas         55 bas.           100 (nm)         0.300 (nm)           0 30 belas         55 bas.           100 (nm)         0.300 (nm)           100 (nm)         0.350 (nm)           100 (nm)         0.300 (nm)           100 (nm)         0.350 (nm)           100 (nm)         0.350 (nm)           100 (nm)         0.350 (nm)           111"         11.4"           114"         3.8"           114"         11.8"           114"         11.8"           114"         11.8"           114"         11.8"           120 (nm)         2.0 (nm)           20 (nm)         2.0 (nm)           20 (nm)         2.0 (nm)           137"         120"           149"         120"           149"         2.0 (nm)           20 (nm)         2.0 (nm)           139 (nm)         2.0 (nm)           140"         0.0 (nm) <t< td=""><td></td><td>R1120</td><td>2557-22</td><td>CTR714A</td></t<>		R1120	2557-22	CTR714A
Baltey included         Baltey included           Baltey included         Baltey included           0         0           100 (nm)         0.200 (nm)           0 200 (nm)         0.200 (nm)           0 30 belas         55 bas.           100 (nm)         0.300 (nm)           0 30 belas         55 bas.           100 (nm)         0.300 (nm)           100 (nm)         0.350 (nm)           100 (nm)         0.300 (nm)           100 (nm)         0.350 (nm)           100 (nm)         0.350 (nm)           100 (nm)         0.350 (nm)           111"         11.4"           114"         3.8"           114"         11.8"           114"         11.8"           114"         11.8"           114"         11.8"           120 (nm)         2.0 (nm)           20 (nm)         2.0 (nm)           20 (nm)         2.0 (nm)           137"         120"           149"         120"           149"         2.0 (nm)           20 (nm)         2.0 (nm)           139 (nm)         2.0 (nm)           140"         0.0 (nm) <t< td=""><td></td><td></td><td></td><td></td></t<>				
Baltey included         Baltey included           Baltey included         Baltey included           0         0           100 (nm)         0.200 (nm)           0 200 (nm)         0.200 (nm)           0 30 belas         55 bas.           100 (nm)         0.300 (nm)           0 30 belas         55 bas.           100 (nm)         0.300 (nm)           100 (nm)         0.350 (nm)           100 (nm)         0.300 (nm)           100 (nm)         0.350 (nm)           100 (nm)         0.350 (nm)           100 (nm)         0.350 (nm)           111"         11.4"           114"         3.8"           114"         11.8"           114"         11.8"           114"         11.8"           114"         11.8"           120 (nm)         2.0 (nm)           20 (nm)         2.0 (nm)           20 (nm)         2.0 (nm)           137"         120"           149"         120"           149"         2.0 (nm)           20 (nm)         2.0 (nm)           139 (nm)         2.0 (nm)           140"         0.0 (nm) <t< td=""><td></td><td>Rare tool</td><td>Ratten included</td><td></td></t<>		Rare tool	Ratten included	
Image: constraint of the sector of the seccor of the sector of the sector of the sector of the sector of			Dattery included	Patton included
260 pm         0.200 pm         350 pm           0.200 pm         0.200 pm         0.300 pm         0.300 pm           30 R4s         50 R4s         33 R4s         33 R4s           10         10 R4s         82 6 R4s         82 2 R4           11/4         11/4*         11/4*         11/4*           11/4*         3/8*         -         -           2 R6         2.84 R6         2.2 R6         2.2 R6           2 R6         2.84 R6         2.2 R6         2.2 R6           11*         11.84*         10.75*           Lion         Lion         Lion         1.44*           2 R6         2.0 R6         2.2 R6         2.2 R6           2 R6         2.0 R6         2.2 R6         2.2 R6           11*         11.84*         10.75*           2 R6         2.0 R6         2.0 R6           2 R6         2.0 R6         2.0 R6           3 R0 R         2.0 R6         2.0 R6           3 R0 R         8.2 R6         8.2 R6           4         4         4.0 R6           5 years tool 3 years hottey         1 year           5 years tool 3 years hottey         1 year           4		Dattery included		Battery included
260 pm         0.200 pm         350 pm           0.200 pm         0.200 pm         0.300 pm         0.300 pm           30 R4s         50 R4s         33 R4s         33 R4s           10         10 R4s         82 6 R4s         82 2 R4           11/4         11/4*         11/4*         11/4*           11/4*         3/8*         -         -           2 R6         2.84 R6         2.2 R6         2.2 R6           2 R6         2.84 R6         2.2 R6         2.2 R6           11*         11.84*         10.75*           Lion         Lion         Lion         1.44*           2 R6         2.0 R6         2.2 R6         2.2 R6           2 R6         2.0 R6         2.2 R6         2.2 R6           11*         11.84*         10.75*           2 R6         2.0 R6         2.0 R6           2 R6         2.0 R6         2.0 R6           3 R0 R         2.0 R6         2.0 R6           3 R0 R         8.2 R6         8.2 R6           4         4         4.0 R6           5 years tool 3 years hottey         1 year           5 years tool 3 years hottey         1 year           4				
260 pm         0.200 pm         350 pm           0.200 pm         0.200 pm         0.300 pm         0.300 pm           30 R4s         50 R4s         33 R4s         33 R4s           10         10 R4s         82 6 R4s         82 2 R4           11/4         11/4*         11/4*         11/4*           11/4*         3/8*         -         -           2 R6         2.84 R6         2.2 R6         2.2 R6           2 R6         2.84 R6         2.2 R6         2.2 R6           11*         11.84*         10.75*           Lion         Lion         Lion         1.44*           2 R6         2.0 R6         2.2 R6         2.2 R6           2 R6         2.0 R6         2.2 R6         2.2 R6           11*         11.84*         10.75*           2 R6         2.0 R6         2.0 R6           2 R6         2.0 R6         2.0 R6           3 R0 R         2.0 R6         2.0 R6           3 R0 R         8.2 R6         8.2 R6           4         4         4.0 R6           5 years tool 3 years hottey         1 year           5 years tool 3 years hottey         1 year           4				
260 pm         0.200 pm         350 pm           0.200 pm         0.200 pm         0.300 pm         0.300 pm           30 R4s         50 R4s         33 R4s         33 R4s           10         10 R4s         82 6 R4s         82 2 R4           11/4         11/4*         11/4*         11/4*           11/4*         3/8*         -         -           2 R6         2.84 R6         2.2 R6         2.2 R6           2 R6         2.84 R6         2.2 R6         2.2 R6           11*         11.84*         10.75*           Lion         Lion         Lion         1.44*           2 R6         2.0 R6         2.2 R6         2.2 R6           2 R6         2.0 R6         2.2 R6         2.2 R6           11*         11.84*         10.75*           2 R6         2.0 R6         2.0 R6           2 R6         2.0 R6         2.0 R6           3 R0 R         2.0 R6         2.0 R6           3 R0 R         8.2 R6         8.2 R6           4         4         4.0 R6           5 years tool 3 years hottey         1 year           5 years tool 3 years hottey         1 year           4		•	•	•
0-200 gm         0-200 gm         0-380 gm           30 0-lis         35 0-lis         33 0-lis           30 0-lis         35 0-lis         34 0-lis           1         46 8-lis         34 2-2 8-lis           1/4"         3/8"				
30 hts         35 hts           76 dBA         62.6 dBA         64.2 dBA           1/4"         1/4"           1/4"         1/4"           1/4"         3/4"           1/4"         3/4"           1/4"         3/4"           1/4"         3/4"           1/4"         3/4"           1/4"         3/4"           1/4"         3/4"           1/4"         3/4"           1/4"         3/4"           1/4"         3/4"           1/4"         3/4"           1/4"         1/4"           1/4"         1/4"           1/4"         1/4"           1/1"         1/18"           1/1"         1/18"           1/1"         1/18"           1/1"         1/18"           1/1"         1/14"           1/1"         1/14"           1/1"         1/14"           1/1"         1/14"           1/1"         1/1"           1/1"         1/1"           1/1"         1/1"           1/1"         1/1"           1/1"         1/1"           1/1"         1/1"				
No data         Add notes           16 data         82.6 data         84.2 data           1/4"         3/8"         1/4"           1/4"         3/8"         -           1/4"         3/8"         -           1/4"         3/8"         -           1/4"         3/8"         -           1/4"         3/8"         -           1/4"         3/8"         -           2 lbs         2.84 lbs         2.2 lbs           11"         11.84"         10.75"           11"         11.84"         10.75"           120         120         120           120         120         120           120         120         120           120         120         144"           120         120         144"           120         120         144"           120         120         144"           120         120         144"           120         120         144"           120         120         144"           13         120         144"           14         120         144"           14         <				
76 dB4         82.5 dBA         84.2 dBA           1/4"         3/8"         1/4"           1/4"         3/8"         -           2 lbs         2.8 lbs         2.2 lbs           2 lbs         2.8 lbs         2.2 lbs           11"         11.84"         10.75"				
1/4"         3/6"           1/4"         3/6"           1         3/6"           1         0           2 hs         2.8 hs           2 hs         2.8 hs           11"         11.84"           12V         12.4 hs           12V         12.4 hs           2.0 hs         2.0 hs           16 ht         2.0 hs           17 fm in         2.0 hs           16 ht         2.0 hs           17 fm in         2.0 hs           16 ht         2.0 ht           17 fm in         2.0 ht           18 mabed         Busiles           18 mabed         Busiles           18 mabed         19 ms           19 ms         19 ms           10 ms         19 ms		76 dBA	82.6 dBA	
1/4"         3/8"           •         •           2 lis         2.2 lis           2 lis         2.2 lis           11"         11.84"           113"         11.84"           114"         10.75"           11"         11.84"           12Y         11.44"           12Y         14.44           2.0 h         2.0 h           3.0 is A         5 min           Writes by application         Writes by application           Budsed         Budsetes           Budsed         Budsetes           Budsed         Budsetes           4         -           5 years tool, 3 years battery         1 year           4         -         -           4         -         -           5 years tool, 3 years battery         1 year           4         -         -           5         -         -           4         -         -           5         -         -				
•         •         •           2 lbs         2.84 lbs         2.2 lbs           11°         11.84°         10.75°           11°         11.84°         10.75°           11°         11.84°         10.75°           11°         11.84°         10.75°           11°         11.44°         10.75°           120         127         14.44           120         2.0 Ah         2.0 Ah           2.0 Ah         2.0 Ah         2.0 Ah           2.0 Ah         2.0 Ah         2.0 Ah           2.0 Ah         2.0 Ah         2.0 Ah           120 min         50 min         2.0 Ah           120 min         2.0 Ah         2.0 Ah           120 Mathed         Bushed         Bushed           Bushed         Bushed         Bushed           120 Mathed         B			3/8"	,
2 lbs         2 lbs         2 lbs           11*         11.84*         10.75*           Liòn         Liòn         Liòn           12Y         12Y         14.44           2.0 An         2.0 An         2.0 An           75 min         20 min         95 min           Waries by application         Waries by application         Waries by application           Bushed         Bushed         Bushes           Bushed         Bushes         Bushed           Maries of a publication         0.35 A           Maries of a publication         0.35 A           Bushed         Bushes         Bushed           Bushed         Bushes         Bushed           Maries of a publication         0         0.35 A           Maries of a publication         0         0.35 A           Maries of a publication         0         0           Maries of a publication				•
11"         11.84"         10.75"           11:0n         11:0n         11:0n           12V         12V         14.4V           2.0 Ah         2.0 Ah         2.0 Ah           2.0 Ah         2.0 Ah         2.0 Ah           15 min         2.0 Min         0.55 min           Veries by application         Veries by application         Brushed           Brushed         Brushes         Brushed           Brushed         Brushes         Brushed           0         0         0         0           1         0         0         0         0           0         0         0         0         0           1         0         0         0         0           1         0         0         0         0           1         0         0         0         0           0         0         0         0         0         0           1         0         0         0         0         0         0         0           0         0         0         0         0         0         0         0         0         0         0 <td< td=""><td></td><td></td><td></td><td></td></td<>				
11"         11.84"         10.75"           11:0n         11:0n         11:0n           12V         12V         14.4V           2.0 Ah         2.0 Ah         2.0 Ah           2.0 Ah         2.0 Ah         2.0 Ah           15 min         2.0 Min         0.55 min           Veries by application         Veries by application         Brushed           Brushed         Brushes         Brushed           Brushed         Brushes         Brushed           0         0         0         0           1         0         0         0         0           0         0         0         0         0           1         0         0         0         0           1         0         0         0         0           1         0         0         0         0           0         0         0         0         0         0           1         0         0         0         0         0         0         0           0         0         0         0         0         0         0         0         0         0         0 <td< td=""><td></td><td>2 lbs</td><td>2.84 lbs</td><td>2.2 lbs</td></td<>		2 lbs	2.84 lbs	2.2 lbs
Li-ion         Li-ion           12V         12V           120         14.4N           2.0.4h         2.0.4h           2.0.4h         2.0.4h           2.0.4h         2.0.4h           2.0.4h         2.0.4h           2.0.4h         2.0.4h           3.0.4         2.0.4h           Wartes ty application         Wartes ty application           Brushed         Brushes         Brushed           Brushed         Brushes         Brushed           0         0         0           1         0         0           1         0         0           1         0         0           1         0         0           1         0         0           1         0         0           1         0         0           0         0         0           1         0         0           1         0         0           1         0         0           1         0         0           1         0         0           1         0         0           1				
12V         12V         14.4V           2.0 Ah         2.0 Ah         2.0 Ah           2.0 Ah         2.0 Ah         2.0 Ah           75 min         20 min         2.0 Ah           Varies by application         Varies by application         Varies by application           Bushed         Bushes         Bushed           Bushed         Bushes         Bushed           0         0         30-35 A           0         0         0         0           1         0         0         0           1         0         0         0           1         0         0         0         0           1         0         0         0         0           1         0         0         0         0           1         0         0         0         0           1         0         0         0         0         0           1         0         0         0         0         0         0           1         0         0         0         0         0         0         0         0         0         0         0         0				
12V         12V         14.4V           2.0 Ah         2.0 Ah         2.0 Ah           2.0 Ah         2.0 Ah         2.0 Ah           75 min         20 min         2.0 Ah           Varies by application         Varies by application         Varies by application           Bushed         Bushes         Bushed           Bushed         Bushes         Bushed           0         0         30-35 A           0         0         0         0           1         0         0         0           1         0         0         0           1         0         0         0         0           1         0         0         0         0           1         0         0         0         0           1         0         0         0         0           1         0         0         0         0         0           1         0         0         0         0         0         0           1         0         0         0         0         0         0         0         0         0         0         0         0		Li-ion	Li-ion	Li-ion
2.0 Ah         2.0 Ah         2.0 Ah           75 min         20 min         55 min           Varies by application         Naries by application         Naries by application           Brushed         Brushed         Brushed           Brushed         Brushed         30-35 Å           -         -         -           -         -         -           -         -         -           3 years         5 years tool, 3 years battary         1 year           -         -         -         -           -         -         -         -           -         -         -         -         -           -         -         -         -         -           -         -         -         -         -           -         -         -         -         -           -         -         -         -         -           -         -         -         -         -           -         -         -         -         -           -         -         -         -         -           -         -         -         -				
Varies by applicationVaries by applicationBushedBushedBushedBushedBushed30.35 AComposition30.35 AComposition30.35 AComposition30.35 AComposition30.35 AComposition9.30.35		2.0 Ah	2.0 Ah	2.0 Ah
BushedBushesBushedImage: Constraint of the second of the secon		75 min	20 min	55 min
Image: Section of Sectio		Varies by application		Varies by application
Image: state s			Brushless	
Image: series of the series				30-35 A
Image: series of the series				
3 years         5 years tool, 3 years battery         1 year           Image: State of St			•	•
Image: Constraint of the constraint		•	•	•
Image: Constraint of the constraint		3 years	5 years tool, 3 years battery	1 year
Image: Constraint of the second of the se				
Image: constraint of the constra		•	•	•
Image: constraint of the sector of the sec		•	•	•
Image: Constraint of the sector of		•	•	•
Rubber overmold1/4" drive socketsCanvas bagCanvas bag		•		
Image: Carry Stage         Carry Stage         Image: C				
Canvas bag           Ca				1/4" drive sockets
•       •       •         •       •       •     <				
Image: Constraint of the constraint			Canvas bag	
Image: Constraint of the constraint				
Image: Constraint of the second se				—
Image: Constraint of the second se		-		-
Image: Constraint of the second sec				•
Image: Constraint of the second se		•	•	
Image: Constraint of the second se		•		
Image: Constraint of the second sec		•		-
Image: Constraint of the second of		•		•
Image: Constraint of the second sec		•		•
				-
				-
Dependable, durable and compact, provides versatility with exceptional performance for tight spaces       First cordless to offer power and size to replace pneumatic ratchets; highest torque cordless ratchets available, according to the company       Fast 350 rpm free speed, variable speed trigger, built-in brake prevents throwing sockets and fasteners		•	•	
Dependable, durable and compact, provides versatility with exceptional performance for tight spaces         First cordless to offer power and size to replace pneumatic ratchets; highest torque cordless ratchets available, according to the company         Fast 350 rpm free speed, variable speed trigger, built-in brake prevents throwing sockets and fasteners				
CACEPtionial periorinance for ugit spaces ingress torque coroless factores dividiable, accoroling to the company brake prevents throwing Sockets and Idstellers	D	ependable, durable and compact, provides versatility with	First cordless to offer power and size to replace pneumatic ratchets;	Fast 350 rpm free speed, variable speed trigger, built-in brake prevents throwing spekts and factorian
		CACEPTIONAL PERIONNANCE IOF USIL SPACES	ingreat torque cortaisas raterieta available, according to the company	שמת אובאבוונים הוויטאוווג מתרעבוים מווע ומסובוובוס

## AIR IMPACT WRENCH - 3/8"

COMPANY NAME	Ingersoll Rand	Mac Tools	Matco Tools		AIRCAT Pneumatic Tools	Chicago Pneumatic Tools	
PRODUCT NAME	3/8" Impact Wrench	High Performance 3/8" Drive Air Impact Wrench	3/8" Composite Impact Wrench		3/8" Composite Com- pact Impact	Compact 3/8" Angle Impact Wrench	
Product model number:	2115TiMAX	MPF990381	MT2138		1076-XL	CP7727	
Price				ш			
Under \$100				N			
\$101-250	•				•		
\$251-500		•	•	S		•	
\$501-1,000				E.			
Over \$1,000							
Manufacturing Specs				-COMPAC			
Composite housing	•		•	Δ	•	•	
Air inlet size	1/4"	1/4"	1/4"	Ξ	1/4"	1/4"	
Air regulator required	,	,	ww		,	,	
Reversible	•	•	•	0	•	•	
Maximum tightening torque	230 ft-lbs	310 ft-lbs	300 ft-lbs	Q	 500 ft-lbs	140 ft-lbs	
Breakaway/nut-busting torque	300 ft-lbs	700 ft-lbs	370 ft-lbs	<b>m</b>	550 ft-lbs	185 ft-lbs	
		0-3,000/0-8,000/0-		D D			
Maximum speed (rpm)	15,000 rpm	9,000/0-10,000 rpm	11,500 rpm	2	9,000 rpm	8,510 rpm	
Air utilization	4 cfm	5.9 cfm	3.5 cfm	<b>MINI/S</b>	4.25 cfm	4 cfm	
Sound level	96.6 dBA	95 dBA	93.5 dBA		85 dBA	104 dBA	
Vibration	7.5 m/2*	5.5 m/s2*			9.9 m/2*	10.3 m/2*	
Dimensions	2.2" x 6.7" x 6.0"	5.6" x 2.5" x 7.8"		Ξ	4.25" x 2.4" x 6.6"	1.18"	
Total weight	2.5 lbs	3 lbs	2.4 lbs		2.5 lbs	2.5 lbs	
Overall tool length	6"	5.6"	5.4"		4.25"	9.4"	
Product Features							
Adjustable torque setting? If yes, how many?	4	4 (3 fwd, 1 rev)	3		3	4	
Built-in work light		•					
Variable speed trigger	•	•	•		•	•	
Length of manufacturer warranty	2 years	2 years	2 years		2 years	1 year	
Hose included	,	,	,		,		
Recommended supply hose	3/8"	3/8"			3/8"	3/8"	
Required cfm	Varies by application	,			8 cfm	4 cfm	
Max PSI	90	90			90	90	
Accessories							
Bare tool available	•	•			•	•	
		_				_	
Includes the following accessories:	Sockets, tune-up kit,						
Other accessories available for purchase separately:	oil, boot	Boot			•		
Comes in a carrying case Application (Mark all that apply)							
Small interior fasteners		•			•	•	
Body panel bolts	•	•	•		•	•	-
	•	•	•		•	•	-
Shroud covers					•		-
Suspension bolts		•				•	
Tire service/lug nuts	•				•	•	
Brake jobs	•	•	•		•		
Engine	•	•	•		•	•	
Interior/exterior work	•	•	•		•		
Under dash		•	•		•	•	
Underhood	•	•	•		•	•	
Tractor/trailer repair		•				•	
Other	Transmission work, general automotive						
Most unique feature	Titanium hammer case offers durability and weight reduction	Trigger activated remov- able and rechargeable LED lighting	Lightweight, compact power impact		AIRCAT patented grip and silencing technology combined with a reliable jumbo hammer mech- anism	Compact, powerful, three positions in forward, one in reverse	



Cornwell Quality Tools	Hazet	Michigan Pneumatic	Mighty-Seven	Monster	OEMTOOLS	Snap-on Tools	SP Air Corporati
3/8" bluePOWER Stub- by Impact Wrench	3/8" Impact Wrench	Venom	3/8" Drive Mini Impact Wrench Quiet version	3/8" Butterfly Impact	Mighty Compact 3/8" Drive Impact Wrench	Impact Wrench	Ultralight Mini Composite Impac Wrench
CAT2138	9011M	MP-7125	NC-3611Q	MST715	24411	MG325	SP-7146EXS
					•		
•	•	•	•	•			
						•	•
					•		•
1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
•	•	•	•		•	•	•
350 ft-lbs	340 ft-lbs	80 ft-lbs	300 ft-lbs	80 ft-lbs	320 ft-lbs	325 ft-lbs	380 ft-lbs
550 ft-lbs	340 ft-lbs	80 ft-lbs	400 ft-lbs			450 ft-lbs	380 ft-lbs
6,500 rpm	6,500 rpm	8,000 rpm	9,000 rpm	12,000 rpm	11,000 rpm	10,700 rpm	10,000 rpm
3 cfm	3 cfm	2.5 cfm	4 cfm	4 cfm	4.7 cfm	2.4 cfm	4 cfm
95 dBA	90.3 dBA	2.5 UIII	4 cm 85 dBA	4 0111	4.7 0111	99.1 dBA	93.1 dBA
95 UBA 7.78 m/2*	90.3 dBA 7.78 m/2*		2.8 m/2*			4.5 m/2*	93.1 dBA 5.5 m/2*
6.75" x 2.25"	3.6" x 2.16" x 6.8"		4.3" x 6.5" x 2.5"	2"	5"	7" x 6.1" x 2.1"	5.2" x 6.5" x 2
3 lbs	2.73 lbs	2.5 lbs	3.3 lbs	1.1 lbs	4.15 lbs	2.8 lbs	2.1 lbs
4.4"	4.49"	4.5"	4.3"	6"	5"	6.1"	5.2"
3	4 (3 fwd, 1 rev)		6 (3 fwd, 3 rev)	Х			4
•			•	Y		•	
2 years	2 years	1 year	3 years	2 years	1 year	2 years	1 year
3/8"	0.4"	3/8"	3/8"	3/8"		3/8"	
5/0	4.49 cfm	2.5 cfm	8 cfm	4 cfm	4.7 cfm	2.4 cfm	4 cfm
90	91.4	90	90			90	90
		•					
•	•	•	•				•
	Coupler plug (nominal size: 7.2)					Boot	
	Silicone protective cover	•	•			Hoses, couplers, filters, regulators	
	cover	•				regulators	
	•	•	•	•		•	•
•	•	•	•	•		•	•
•	•	•	•	•		•	•
•	•			•		•	
•	•	•	•	•		•	•
•	•	•	•	•		•	•
•	•	•	•	•		•	•
	•	•	•	•			
•	•	•	•	•		•	•
•		•				•	•
Transmission, drivetrain							
Stubby design with jumbo hammer mech- anism delivers high power to size ratio	Combination of small dimensions and power with a 3/8" drive	Streamlined design offers lightweight solution with full lever throttle	Ultra light with a compact profile, perfect for tight access applications	The only 1/4" drive Nano size butterfly impact wrench on the market, according to the company	Unique size fits into spaces that regular size impact wrenches do not, according to the company	Compact, lightweight, powerful, twin hammer, oil bath impact mecha- nism lubrication	Ultra light weight 2.14 lbs

## AIR IMPACT WRENCH - 1/2"

COMPANY NAME	AIRCAT Pneumatic Tools	Ingersoll Rand	Snap-on Tools	Mac Tools	Matco Tools	Michigan Pneumatic	
PRODUCT NAME	1/2" AIRCAT Vibrotherm Drive Impact Wrench	1/2" Impact Wrench	Impact Wrench	High Performance 1/2" Drive Air Impact Wrench	1/2" Impact Wrench	Venom	
Product model number:	1178-VXL	2235TiMAX	PT850	MPF990501	MT2769	MP-2144QR	
Price							
\$101-250	•					•	
\$251-500		•		•	•		
\$501-1,000			•				
Over \$1,000							
Manufacturing Specs							
Composite housing	•	•	•		•	•	
Air inlet size	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	
Air regulator required Reversible	•	•	•	•	•	•	
			600 ft-lbs fwd, 810				
Maximum tightening torque	900 ft-lbs	900 ft-lbs	ft-lbs rev	580 ft-lbs	850 ft-lbs	900 ft-Ibs	
Breakaway/nut-busting torque	1,300 ft-lbs	1,350 ft-lbs	1,190 ft-lbs	1,400 ft-lbs	1,300 ft-lbs	900 ft-Ibs	
Maximum speed (rpm)	7,500 rpm	8,500 rpm	9,200 rpm	0-2,200/0-4,500/0- 5,500/0-6,500 rpm	7,500 rpm	8,000 rpm	
Air utilization	8 cfm	6 cfm	4.1 cfm	6.1 cfm	4.9 cfm	6.7 cfm	
Sound level	84 dBA	98 dBA	98.1 dBA	94 dBA	99.8 dBA	0.7 0111	
Vibration	10.2 m/s2*	9 m/s2*	8.2 m/s2*	6.4 m/s2*	0010 0011		
Dimensions	6.4" x 2.75" x 7.75"	2.9" x 7.2" x 7.6"	7.5" x 7.2" x 3.0"	6.4" x 3" x 8.3"			
Total weight	4.5 lbs	4.6 lbs	4.2 lbs	4.8 lbs	4.6 lbs	5 lbs	
Overall tool length	6.4"	7.6"	7.2"	6.4"	7.5"	7.75"	
Product Features							
Adjustable torque setting? If yes, how many?	3	4		•	4		
Built-in work light				•			
Variable speed trigger	•	•	•	•	•	•	
Length of manufacturer warranty	3 years	2 years	2 years	2 years	2 years	1 year	
Length of limited warranty vs. unlimited warranty	3 years		2 years	2 years	2 years	1 year	
Hose included	2.401	- (OII	5.10H	- 10 H	- 10 H	- 10 <b>1</b>	
Recommended supply hose	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	
Required cfm	8 cfm	Varies by application	4.1 cfm	00	00	6.7 cfm	
Max PSI	90	90	90	90	90	90	
Accessories	•	•		•		•	
Bare tool available	•	•		•		•	
Includes the following accessories:			Boot				
Other accessories available for purchase separately:	•	Sockets, tune-up kits, oil, boot	Hoses, couplers, filters, regulators	Boot		•	
Comes in a carrying case							
Application (mark all that apply)							
Small interior fasteners				•			<u> </u>
Body panel bolts	•			•		•	
Shroud covers	•		•	•			
Suspension bolts	•	•	•	•	•	•	
Tire service/lug nuts	•	•	•	•	•	•	
Brake jobs		•	•	•	•	•	
Engine	•	•	•	•	•	•	
Interior/exterior work	•	•		•	•	•	
Under dash		_	_	•	_		
Underhood	•	•	•	•	•		
Tractor/trailer repair		•		•	•	•	
Other		General automotive	Heavy Duty Truck, AG and construction				
Most unique feature	New patent pending impact mechanism reducing vibration by 30 percent and increasing life by 50 percent, according to the company	Titanium hammer case offers durability and weight reduction	Powerful 810 ft-lbs, forged anvil, frame and twin hammers for long life	Trigger activated removable and rechargeable LED lighting	Powerful, great weight to power ratio, according to the company	Incredible power-to- weight ratio, according to the company; durable lightweight composite housing	



Chicago Pneumatic Tools	Cornwell Quality Tools	Hazet	Legacy Manufacturing	Mighty-Seven	Monster	OEMTOOLS	Puma Tools	SP Air Corporation
Compact 1/2"	1/2" bluePOWER Stubby Impact	1/2" Impact Wrench	Flexzilla Pro Mini Impact Wrench	1/2" Drive Mini Impact Wrench	Monster Mini 1/2" Composite Impact	1/2" Drive Compact Air Impact	1/2" Air Impact	Ultralight Mini Composite Impact
CP7732C	Wrench CAT4112	9012M	AT8505FZ	Quiet version NC-46120	Wrench MST7126	Wrench 24418	AT5646	Wrench SP-7146EX
CF1152C	CA14112	901210	AIOJUJIZ	NC-4012Q	W317120	24410	A15040	JF-7140EX
	•	•	•	•	•	•	•	
•								•
•			٠		٠	•		•
1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
							•	
•	•	•	•	•	•	•	•	•
285 ft-lbs	450 ft-lbs	500 ft-lbs	550 ft-lbs	400 ft-lbs	450 ft-lbs	900 ft-lbs	400 ft-lbs	440 ft-Ibs
460 ft-lbs	600 ft-lbs	811 ft-lbs	800 ft-lbs	700 ft-lbs	600 ft-lbs		500 ft-lbs	440 ft-Ibs
1,400 rpm	9,000 rpm	10,000 rpm	9,500 rpm	9,000 rpm	10,000 rpm	10,000 rpm	9,000 rpm	10,000 rpm
5.5 cfm	3 cfm	4.49 cfm	4.8 cfm	4.4 cfm	5 cfm	4 cfm	5 cfm	4 cfm
106.5 dBA	95 dBA	97.1 dBA		85 dBA			83 dBA	93.1 dBA
10.8 m/s2*	10.02 m/s2*	9.57 m/s2*		2.8 m/s2*	0"		0.511 40.411 0.41	5.5 m/s2*
1.26" 2.2 lbs	6-3/4" x 2-1/4" 3 lbs	3.6" x 2.16" x 6.8" 2.73 lbs	4.4" 2.5 lbs	4.5" x 2.4" x 7.5" 3.9 lbs	3" 2.9 lbs	2.8 lbs	3.5" x 10.4" x 2.4" 2.78 lbs	5.2" x 6.5" x 2" 2.1 lbs
4.3"	4.4"	4.49"	4.4"	4.5"	5"	4.5"	3.46"	5.2"
4	3	4 (3 fwd, 1 rev)	3	4 (3 fwd, 1 rev)	4		6 (3 fwd, 3 rev)	4
• 1 year	2 years	2 years	1 year	<ul> <li>3 years</li> </ul>	2 years	1 year	1 year	1 year
1 year	2 years	2 years	1 year	5 years	2 years	1 year	1 year	1 year
			•			,		
3/8"	3/8"	3/8"		3/8"	3/8"		3/8"	440
5.5 cfm		4.49 cfm	4.8 cfm	8 cfm	5 cfm		5 cfm	4 cfm
90	90	91.4	175	90	90		115	90
•	•	•	•	•				•
		Coupler plug	50 '. Air Hose, 8 High					
		(nominal size: 7.2) Silicone protective	Flow Couplers and Plugs					
		cover		•				
		•	•	•	•			
		•	•	•	•			•
	•	•	•	•	•			
•	•	•	٠	•	٠			•
•	•	•	•	•	•			
•	•	•	•	•	•			•
•	•	•	•	•	•			•
	•	•	•	•	•			•
	•	•	•	•	•			•
	•		•	•	•			•
	Transmission, drivetrain							
Ultra lightweight, compact, powerful and durable	Stubby design with jumbo hammer mechanism delivers high power to size ratio	Combination of small dimensions and power	Features 800 ft-lbs of nut-busting break- away torque and an extremely lightweight design	Incredible power- to-weight ratio, easy access to confined work areas, according to the company	Smallest, lightest mini 1/2" on the market, highest power-to- weight ratio in the automotive service industry, according to the company	Designed with a unique compact body allowing it to fit in spaces regular impact wrenches do not	N/A	Ultra light weight of 2.14 lbs

## AIR IMPACT WRENCH - 3/4"

COMPANY NAME	AIRCAT Pneumatic Tools	Cornwell Quality Tools	Ingersoll Rand	Matco Tools	Michigan Pneumatic	
PRODUCT NAME	3/4" AIRCAT Vibrotherm Drive Impact Wrench	3/4" bluePOWER Super Duty Impact Wrench	3/4" Impact Wrench	3/4" Impact Wrench	Venom	
Product model number:	1778-VXL	CAT3125	2145QiMAX	MT2234	MP-2146QR	
Price						
\$101-250	•					
\$251-500					•	
\$501-750		•	•			
\$751-1,000				•		
Over \$1,000						
Manufacturing Specs						
Composite housing	•	•	•	•	•	
Air inlet size	3/8"	3/8"	3/8"	3/8	3/8	
Air regulator required						
Reversible	•	•	•	•	•	
Maximum tightening torque	1,400 ft-lbs	1,200 ft-Ibs	1,100 ft-lbs	1,200 ft-lbs	1,300 ft-lbs	
Breakaway/nut-busting torque	1,700 ft-lbs	1,800 ft-lbs	1,700 ft-lbs	1,800 ft-lbs	1,300 ft-lbs	
Maximum speed (rpm)	5,500 rpm	6,000 rpm	7,000 rpm	6,000 rpm	6,000 rpm	
Air utilization	8 cfm	6.9 cfm	8 cfm	6.9 cfm	7.3 cfm	
Sound level	95 dBA	97.3 dBA	96.3 dBA	97.3 dBA		
Vibration	14.2 m/s2*		8.7 m/s2*			
Dimensions	7.4" x 3.6" x 8.25"	8.625" x 3.125"	3.3" x 8.1" x 8.5"			
Total weight	7.4 lbs	6.9 lbs	7.4 lbs	6.8 lbs	8.2 lbs	
Overall tool length	7.4"	8"	8.5"	8"	8.6875"	
Product Features						
Adjustable torque setting? If yes, how many?	3	3	4	4		
Built-in work light						
Variable speed trigger	•	•	•	•	•	
Length of manufacturer warranty	3 years	2 years	2 years	2 years	1 year	
Length of limited warranty vs. unlimited warranty	3 years			2 years	1 year	
Hose included	4 (0)	4 (0"	4.(0)"		4 (0"	
Recommended supply hose	1/2"	1/2"	1/2"		1/2"	
Required cfm	8 cfm	00	Varies by application		7.3 cfm	
Max PSI	90	90	90		90	
Accessories						
Bare tool available	•	•	•		•	
Includes the following accessories:						
Other accessories available for purchase separately:	•		Sockets, tune-up kits, oil, boot		•	
Comes in a carrying case						
Application (Mark all that apply)						
Small interior fasteners						
Body panel bolts	•					
Shroud covers						
Suspension bolts	•	•	•	•	•	
Tire service/lug nuts	•	•	•	•	•	
Brake jobs		•	•	•	•	
Engine	•	•	•	•	•	
Interior/exterior work			•	•		
Under dash						
Underhood	•	_	•	•	_	
Tractor/trailer repair	•	•	•	•	•	
Other			General automotive			
Most unique feature	New patent pending impact mechanism, reducing vibration by 30 percent and increasing life by 50 percent	Easy-to-use forward and reverse lever improves comfort and efficiency	This tool is lightweight and features a quiet design while maintaining durability	Lightweight impact wrench, 1,800 ft-lbs of breakaway torque, forward/reverse lever accommodates left- and right-hand users	Incredible power-to-weight ratio, according to the com- pany; durable lightweight composite housing	

### PTEN

OEMTOOLS	Puma Air	Snap-on Tools
3/4" Drive Heavy Duty Air Impact Wrench	3/4" Air Impact	Impact Wrench
25810	AT5261	MG1250
•	•	
		•
	•	
3/8"	3/8"	3/8"
	•	
•	•	•
1,300 ft-lbs	1,050 ft-lbs	1,150 ft-lbs fwd,
2,000 10 100		1,250 ft-lbs rev 1,750 ft-lbs
 4,400 rpm	1,150 ft-lbs	6,200 rpm
4,400 rpm	6,500 rpm	6.4 cfm
 0.0 Cilil	98 dBA	99.8 dBA
	90 UDA	10.3 m/s2*
	8.7" x 8.7" x 3.5"	9.5" x 8.15" x 3.25"
 14 lbs	8.16 lbs	8.1 lbs
14 105	8,74"	8.15"
	0,11	0.10
	5 (4 fwd, 1 rev)	
	5 (4 IWd, 1 ICV)	
		•
1 year	1 year	2 years
1 year		2 year
	1/2"	3/8"
	16 cfm	6.4 cfm
	115	90
	•	
		Boot
	•	Air hoses, couplers, filters, regulators
		loguidelis
	•	•
	•	•
		•
		•
	•	•
	•	•
		Heavy duty truck, agriculture, heavy duty equipment
Pin clutch mechanism and handle exhaust reduce vibration and noise output, provide high torque output		Powerful, fast motor start- up, multiple anvil lengths available

	Chicago Pneumatic Tools	Hazet	Mighty-Seven	SP Air Corporation
	3/4" Stubby Impact Wrench	3/4" Impact Wrench	3/4" Drive Composite Impact Wrench Quiet version	Composite Impact Wrench
1.1	CP7762	9013M	NC-6255Q	SP-7150-V8
N				
0)		•	•	
	•			•
0				
A				
F			•	•
Z	3/8"	3/8"	1/4"	3/8"
2				
9	•	•	•	•
Ö	670 ft-lbs	800 ft-lbs	1,100 ft-lbs	1,100 ft-lbs
	1,050 ft-lbs	1,394 ft-lbs	1,400 ft-lbs	1,100 ft-lbs
S	4,850 rpm	7,300 rpm	8,500 rpm	4,300 rpm
MINI/SUB-COMPACT SIZE	8.78 cfm	5.4 cfm		6 cfm
Z	103.8 dBA	104 dBA	85 dBA	94.9 dBA
5	10.7 m/s2* 1.65"	7.47 m/s2* 7.4" x 2.83" x 7.64"	4.7 m/s2* 8" x 3" x 8"	9 m/s2* 9.3" x 9" x 3"
	6.38 lbs	4.63 lbs	4.5 lbs	7.9 lbs
	6.2"	7.4"	8"	9.3"
		4 (3 fwd, 1 rev)	4 (3 fwd, 1 rev)	4
	1 year	2 years	• 3 years	1 year
	1 year	2 yours	5 years	1 year
	<b>,</b>			
	1/2"	0.4"	3/8"	
	8.78 cfm	7.4 cfm	9 cfm	6 cfm
	90	91.4	90	90
	•	•	•	•
		Coupler plug		
		(nominal size: 7.2)		
			•	
			•	
	•	•	•	•
	•		•	
	•		•	•
		•		
			-	
	•	•	•	•
		SUV, trucks, agricultural and transport vehicles, industrial machines, naval constructions		
	Ultra compact, powerful, twin hammer clutch	3/4" impact wrench in 1/2" housing size with enormous power, according to the company	3/4" impact wrench built in 1/2" size body; quiet version 85 dBA operating sound pressure	Convenient SAS (side and side) system offers forward/ reverse for one-handed operation

## AIR IMPACT WRENCH - 1"

COMPANY NAME	AIRCAT Pneumatic Tools	Chicago Pneumatic Tools	Cornwell Quality Tools	Hazet	Ingersoll Rand	
PRODUCT NAME	1" Super Duty Ext. Anvil Impact Wrench	1" Torque Limited Impact Wrench	1" bluePOWER Impact Wrench with 6" Extended Anvil	1" Impact Wrench With Long Spindle	1" Impact Wrench	
Product model number:	1992	CP7782TL-6	CAT6156BP	9014P-1	2850MAX	
Price						
Under \$100						
\$101-250						
\$251-500	•					
\$501-750					•	
\$751-1,000			•	•		
Over \$1,000		•				
Manufacturing Specs						
Composite housing			•		•	
Air inlet size	1/2"	1/2"	1/2"	1/2"	1/2"	
Air regulator required						
Reversible	•	•	•	•	•	
Maximum tightening torque	1,600 ft-lbs	325 ft-lbs	2,000 ft-lbs	2,000 ft-lbs	2,000 ft-lbs	
Breakaway/nut-busting torque	1,800 ft-lbs	1,920 ft-lbs		2,507 ft-lbs	2,100 ft-lbs	
Maximum speed (rpm)	5,000 rpm	5,200 rpm	6,200 rpm	5,500 rpm	5,500 rpm	
Air utilization	12 cfm	10 cfm	9 cfm	10 cfm	14 cfm	
Sound level		111 dBA	104.1 dBA	103.5 dBA	96.7 dBA	
Vibration		7.8 m/s2*	13 m/s2*	15.94 m/s2*	10.3 m/s2*	
Dimensions	23.2" x 8.5" x 7.25"	8.29"	9" x 8"	23.1" x 7.4" x 7.28"	13.1" x 4.4" x 7.9"	
Total weight	26 lbs	25.55 lbs	17.8 lbs	18.9 lbs	19.4 lbs	
Overall tool length	23.2"	20.11"	19.8"	23.1"	13.1"	
Product Features						
Adjustable torque setting? If yes, how many?	3	4	4	6 (3 fwd, 3 rev)	3	
Built-in work light						
Variable speed trigger	•	•	•		•	
Length of manufacturer warranty	2 years	1 year	2 years	2 years	2 years	
Length of limited warranty vs. unlimited warranty	2 years	1 year				
Hose included						
Recommended supply hose	1/2"	1/2"	3/4"	3/4"	3/4"	
Required cfm	12 cfm	10 cfm		10 cfm	Varies by application	
Max PSI	90	90	90	91.4	90	
Accessories						
Bare tool available	•	•	•	•	•	
Includes the following accessories:				Coupler plug (nominal size: 10)		
Other accessories available for purchase separately:					Sockets, tune-up kit, oil	
Comes in a carrying case						
Application (Mark all that apply)						
Small interior fasteners						
Body panel bolts						
Shroud covers						
Suspension bolts					•	
Tire service/lug nuts	•	•	•		•	
Brake jobs		•			•	
Engine						
Interior/exterior work						
Under dash						
Underhood						
Tractor/trailer repair	•	•	•	•	•	
Other				Truck tires	Heavy equipment, off-road vehicles	
Most unique feature	Features 8" anvil with combined friction ring and through hole, twin hammer mechanism and D handle	Torque limited, same power in reverse as the CP7782-6	Durable composite housing withstands tough environments and reduces weight	Long spindle (9.45") for optimal accessibility of wheel bolts	Provides the ultimate in power-to-weight ratio by delivering class-leading torque packaged in a lighter weight design	

### PTEN

Matco Tools	Michigan Pneumatic	Mighty-Seven	OEMTOOLS	Puma Air	Snap-on Tools		SP Air Corporation
Silver Eagle 1" Drive Impact Wrench	Venom	1" Drive Impact Wrench	1" Drive Heavy Duty Extended Anvil Impact Wrench	1" Air Impact	Impact Wrench		Impact Wrench
SE116	MP-2148QR	NC-8343-8	25811	AT5380-6	PT1800A		SP-1194DX-6
						Ш	
						N	
 						S	
 	_	•	•	_			
 •	•			•		C	
					•		•
						6	
	•			•		-COMPA	
1/2"	3/8"	1/2"	1/2"	1/2"	3/8"	5	1/2"
,	,	,	,	•	,	X	,
•	•	•	•	•	•	Y	•
1,600 ft-lbs	1,400 ft-lbs	1,600 ft-lbs	1,600 ft-lbs	1,600 ft-lbs	1,800 ft-lbs	m	1,800 ft-lbs
1,200 ft-lbs	1,400 ft-lbs	2,100 ft-lbs		1,750 ft-lbs			1,800 ft-lbs
4,000 rpm	6,000 rpm	5,000 rpm	3,700 rpm	5,000 rpm	6,500 rpm	S	4,800 rpm
10 cfm	7.3 cfm	11 cfm	16 cfm		8.6 cfm		7.2 cfm
98.8 dBA		103 dBA	112.2 dBA	106 dBA	104 dBA	Ζ	98 dBA
		6.3 m/s2* 23" x 7" x 5"		19.2" x 7.3" x 6.7"	8.5 m/s2* 5.5" x 3.75" x 20"	MINI	14.2 m/s2* 20.6" x 7" x 3.5"
25.7 lbs	8.42 lbs	23 X 7 X 5 29 lbs	29.8 lbs	19.2" X 7.3" X 0.7" 17.86 lbs	15.2 lbs	2	17.2 lbs
23.7 103	8.42"	23 103	19.7"	19.17"	20"		20.6"
22	0.42	20	15.7	15.17	20		20.0
		6 (3 fwd, 3 rev)		6 (3 fwd, 3 rev)			
							•
•	•	•			•		
1 year	1 year	1 year	1 year	1 year	1 year		1 year
1 year	1 year		1 year		1 year		1 year
	1/2"	1/2"		1/2"	1/2"		
	7.3 cfm	19 cfm	16 cfm	19 cfm	8.6 cfm		7.2 cfm
	90	90	90	90	90		90
	•	•		•			•
	•	•		•			
	•	•		•	Air hoses, couplers, filters,		
	-	-		_	regulators		
•	•	•			•		
•	•	•		•	•		
		•			•		
	•	•			•		
					•		
•	-			•	•		-
•	•	•		•	Heavy duty equipment,		•
					construction and AG		
Value priced 1" impact	Incredible power-to- weight ratio, according to the company; durable lightweight composite housing	One of the most cost-effective tools within its class, according to the company	Features a 6" extended anvil for deep truck wheels; rocking clutch is ideal for tire work		Twin hammer impact, side directed exhaust, lightweight design, padded side handle		1,800 ft-lbs of torque, higher torque for stub- born fasteners and light- weight aluminum housing weighing 17.2 lbs

## AIR RATCHET - 3/8"

COMPANY NAME	AIRCAT Pneumatic Tools	Cornwell Quality Tools	Ingersoll Rand	Matco Tools	Michigan Pneumatic	Monster	
PRODUCT NAME	3/8" Composite Twin Pawl Ratchet	3/8" Heavy Duty Air Ratchet	3/8" High Torque Ratchet	3/8" Composite Air Ratchet	Speed Ratchet	3/8" High power Ratchet	
Product model number:	802	CAT5500HD	109XPA	MT2854	MP-7131-ST	MST7108	
Price							
Under \$100	•				•		
\$101-250		•	٠			•	
\$251-500				•			
Manufacturing Specs							
Composite housing	•	•		•	•		
Air inlet size	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	
Air regulator required							
Reversible	•		•	•	•		
Max tightening torque	70 ft-lbs	90 ft-lbs	76 ft-lbs	100 ft-lbs	90 ft-Ibs	100 ft-lbs	
Breakaway/nut-busting torque	70 ft-lbs				90 ft-lbs		
Maximum speed (rpm)	280 rpm	190 rpm	220 rpm	200 rpm	600 rpm	600 rpm	
Air utilization	4 cfm	4 cfm	4 cfm	3.3 cfm	4 cfm	4 cfm	
Sound level	82 dBA	99 dBA	92.4 dBA	88 dBA			
Vibration	3.2 m/s2*		2.5 m/s2*				
Dimensions	10.5" x 1.7" x 2.1"		12"			3"	
Total weight	2.75 lbs	2.8 lbs	3.3 lbs	2.5 lbs	2.78 lbs	3.97 lbs	
Overall tool length	10.5"	10.8"	12"	10.2"	10.875"	10"	
Product Features							
Adjustable torque setting						•	
Built-in LED							
Variable speed trigger	•	•	•	•		•	
Length of manufacturer warranty	2 years	1 year	1 year	1 year	1 year	2 years	
Length of limited warranty v. unlimited warranty	2 years	1 9001	1 jour	1 year	1 year	2 jouro	
Hose included	2 joure			1 )001	1 jour		
Recommended supply hose	3/8"	3/8"	3/8"			3/8"	
Accessories	0/0	0/0	0/0			0,0	
Bare tool available	•	•	•		•		
Includes the following accessories:							
Other accessories available for purchase separately:	•		Sockets, tune-up kits, oil		•		
Comes in a carrying case							
Application (Mark all that apply)							
Small interior fasteners		•		•	•		
Body panel bolts	•	•	•	•	•	•	
Shroud covers	•	•		•	•	•	
Suspension bolts		•				•	
Tire service/lug nuts							
Brake jobs	•	•			•	•	
Engine	•	•	•	•	•	•	
Interior/exterior work	•	•	•	•	•	•	
Under dash	•	•		•	•	•	
Underhood	•	•	•	•	•	•	
Tractor/trailer repair		•			•		
Other			Mufflers, general automotive				
Most unique feature	Patented AIRCAT ex- haust system, durable twin pawl mecha- nism, ergonomically designed housing	High torque design helps to remove stubborn fasteners	360-degree adjust- able directs the air flow away from the user and workspace	Powerful ratchet in lightweight composite housing	Dual hammer pin impact mechanism delivers smooth blows and high torque	Weighs only 3.97 Ibs	



OEMTOOLS	Puma Air	Snap-on Tools	
3/8" Drive Super Duty Air Impact Ratchet	Impact Ratchet Wrench	Air Ratchet	
24416	AT5350	PTR72	
24410	A13330	FIR72	
•			
-	•		
		•	C
•			
1/4"	1/4"	1/4"	5
_/ ·	•		
•	•	•	
50 ft-lbs	50 ft-lbs	70 ft-lbs	2
	55 ft-lbs		
700 rpm	400 rpm	275 rpm	(
3.1 cfm		4.5 cfm	
	92 dBA	92.9 dBA	5
	52 05/1	5.2 m/s2*	
6.5"	11.6" x 1.9" x 2.2"	11.8"	g
1.32 lbs	2.78 lbs	2.9 lbs	
6.5"	11.61"	11.8"	2
0.0	11.01	11.0	
			2
		•	
1 year	1 year	2 years	
1 year	1 )001	2 years	
1 )001		2 )0010	
	3/8"	3/8"	
	6/ 6	0,0	
	•		
	-		
		Boot	
		Air hoses, couplers,	
	•	filters, regulators	
	•	•	
	•	•	
	•	•	
		•	
		•	
	•	•	
	•	•	
	•	•	
		•	
		•	
Provides three times		With the 1 450 G II	
Provides three times the work efficiency		Withstands 158 ft-lbs manual torque: steel	
		Withstands 158 ft-lbs manual torque; steel wear bushings reduce ratchet head wear	

Chicago Pneumatic Tools	Hazet	Legacy Manufacturing	Mighty-Seven	SP Air Corporatio
3/8" Composite Air Ratchet	PI3/8" Air Ratchet	Flexzilla Pro Reaction- less Mini Air Ratchet	3/8" Drive Mini Im- pact Ratchet Wrench	Super Fast Mini Impact Ratchet
CP825CT	9021P-2	AT8535FZ	NC-3920	SP-1765HD
	•	•	•	•
•				
•				
_	1 / 4"	1/4"	1 / 4"	1 / 4"
1/4"	1/4"	1/4	1/4"	1/4"
•	•	•	•	•
26 ft-lbs	39.8 ft-lbs	45 ft-lbs	35 ft-Ibs	55 ft-lbs
26 ft-lbs	39.8 ft-lbs	3.5 ft-lbs	37 ft-Ibs	55 ft-lbs
280 rpm	300 rpm	700 rpm	230 rpm	700 rpm
3.2 cfm	3.64 cfm	3.5 cfm	4.6 cfm	2.3 cfm
93 dBA	92 dBA		88 dBA	84.4 dBA
4 m/s2*	3.9 m/s2*		3 m/s2*	2.9 m/s2*
1.5" x 1.4"	5.9" x 1.55" x 2"		7" x 2.5" x 2.25"	6.9" x 1.5" x 1"
1.1 lbs	1.1 lbs	1.5 lbs	1.1 lbs	1.4 lbs
6.6"	5.9"	7.5"	6.9"	6.9"
				•
•			•	
1 year	2 years	1 year	3 years	1 year
1 year				1 year
		•		
1/4"	0.4"		3/8"	
•	•		•	•
	Coupler plug (nominal size: 7.2)	Custom Length Whip Hose with High Flow Ball Swivel, High Flow Couplers and Plugs, 2		
		Couplers, 2 Plugs		
Sockets, hose reel, hoses			•	
•	•	•	•	
•	•	•	•	•
•		•	-	•
•				•
		•		
	٠	•		•
•	٠	•	•	•
•	٠	•	•	•
	٠	•	•	•
		•		•
Lightweight, better speed control, flat forward and reverse button	Closed head avoids entry of swarf	Compact and light- weight design perfect for small workspaces, according to the company	3/8" drive anvil includes 1/4" bit holder; ideal for tight access applications	Patented single dog clutch impact mechanism provide a maximum speec of 700 rpm with a maximum torque o 55 ft-lbs

## AIR RATCHET - 1/2"

COMPANY NAME	AIRCAT Pneumatic Tools	Hazet	Ingersoll Rand	
PRODUCT NAME	1/2" High Torque Ratchet	1/2" Air Ratchet	1/2" High Torque Ratchet	
Product model number:	805-HT-5	9022P-2	1099XPA	
Price				
Under \$100				
\$101-250	•	•	•	
\$251-500				
Manufacturing Specs				
Composite housing	•			
Air inlet size	1/4"	1/4"	1/4"	<u> </u>
Air regulator required		-/ .		<u> </u>
Reversible	•	•	•	
Max tightening torque	130 ft-lbs	80 ft-lbs	76 ft-lbs	
Breakaway/nut-busting torque	130 ft-lbs	80 ft-lbs	1010105	<u> </u>
Maximum speed (rpm)	180 rpm	280 rpm	220 rpm	
Air utilization	6 cfm	4 cfm	4 cfm	
Sound level	84 dBA	99 dBA	92.4 dBA	
Vibration	6.6 m/s2*	9.1 m/s2*	2.5 m/s2*	<u> </u>
Dimensions	12.45" x 2.10" x 2.10"	12.25" x 1.9" x 2.17"	12"	
Total weight	3.3 lbs	2.73 lbs	3.3 lbs	<u> </u>
Overall tool length	12.45"	12.25"	12"	
Product Features	12.43	12.25	12	
Adjustable torque setting				
Built-in LED				
Variable speed trigger	•		•	
Length of manufacturer warranty	2 years	2 years	1 year	<u> </u>
Length of Imited warranty v. unlimited warranty	2 years	2 years	1 year	
Hose included	2 jours			
Recommended supply hose	3/8"	0.4"	3/8"	-
Accessories	3,0	0.4	5/0	
Bare tool available	•	•	•	
	•	-	•	
Includes the following accessories:	•	Coupler plug (nominal size: 7.2)	Cookota tuno un kita ail	
Other accessories available for purchase separately:	•		Sockets, tune-up kits, oil	
Comes in a carrying case				
Application (Mark all that apply)				
Small interior fasteners		•		
Body panel bolts		•	•	
Shroud covers	•	•		
Suspension bolts				<u> </u>
Tire service/lug nuts				
Brake jobs	•	•		<u> </u>
Engine	•	•	•	
Interior/exterior work	•	•	•	ļ
Under dash		•		
Underhood	•	•	•	
Tractor/trailer repair				
Other			Mufflers, general automotive	
Most unique feature	AIRCAT patented Silencing technology with reliable latest ratchet head design		360-degree adjustable exhaust directs the air flow away from the user and workspace	



Michigan Pneumatic	Mighty-Seven	SP Air Corporation		Chicago Pneumatic Tools
Speed Ratchet	1/2" Drive Ratchet Wrench with Dual Stage Power Trigger	Heavy Duty Sealed Flat Head Ratchet		1/2" Ratchet
MP-7132-ST	NE-483	SP-7787		CP7829H
			SIZE	
•	•			
			S –	
		•		•
•			<b>B-COMPACT</b>	•
1/4"	1/4"	1/4"		1/4"
				_/ -
•	•	•		
90 ft-lbs	65 ft-lbs	80 ft-lbs	0	55 ft-lbs
90 ft-lbs	100 ft-lbs	80 ft-lbs	Ö	70 ft-lbs
600 rpm	250 rpm	200 rpm	T	225 rpm
		3.5 cfm		10.95 cfm
	85 dBA	84.5 dBA	$\mathbf{D}$	85 dBA
	2 m/s2*	3.6 m/s2*	S	8.6 m/s2*
0.00.1	11" x 2" x 2"	12" x 1.5" x 1"		0.70.11
2.82 lbs	2.8 lbs	3.3 lbs	Z	2.73 lbs
11"	10.9"	12"	<b>NIN</b>	10.7"
				•
1 year	3 years	1 year		1 year
1 year		1 year		1 year
	3/8"			1/2"
•	•	•		•
			_	
•	•		_	Sockets, hoses
•	•			•
•	•			•
-	•			•
•				•
•	•			
•	•	•		•
•	•			
•	•			•
•	•			٠
•		•	_	
			_	
Dual hammer pin impact mechanism delivers smooth blows and high torque	Innovative dual stage power, operates at a low vibration level	Patented sealed flat ratchet mechanism	C	compact, powerful, lightweight and versati according to the company

### PRODUCTS



Milwaukee M12 FUEL Stubby Impact Wrenches Enter 102 at "e-inquiry" on VehicleServicePros.com



Ingersoll Rand Ingersoll Rand 2850MAX 1" D-Handle Impact Wrench Enter 103 at "e-inquiry" on VehicleServicePros.com



Legacy Manufacturing Flexzilla Pro Reactionless Mini Air Ratchet Kit, No. AT8535FZ Enter 104 at "e-inquiry" on VehicleServicePros.com



High Performance Air Ratchet, No. 9022-360 Enter 105 at "e-inquiry" on VehicleServicePros.com



A Pneumatic 3/4" Impact Wrench, No. CP7769 Enter 106 at "e-inquiry" on VehicleServicePros.com



AIRCAT Pneumatic Tools 1/2" High Torque Ratchet, No. 805-HT-5 Enter 107 at "e-inguiry" on

VehicleServicePros.com



Mighty-Seven 3/8" Drive Mini Impact Ratchet, No. NC-3920 Enter 108 at "e-inquiry" on VehicleServicePros.com



1/2" Drive Aluminum Impact Wrench, No. MPF970501

Enter 109 at "e-inquiry" on VehicleServicePros.com Makita 12V Max 3/8" Right Angle Drill Enter 110 at "e-inquiry" on VehicleServicePros. com



Air Reversible Flex Head Cut-Off Tool, No. SP-7231R Enter 111 at "e-inquiry" on VehicleServicePros.com



20V MAX Li-ion Brushless Impact Wrench, No. 24486 Enter 112 at "e-inquiry" on VehicleServicePros.com

#### **Matco Tools**

16V Cordless Infinium 1/4" Drive High Performance Impact Driver Kit, No. MCL1614HPIDK Enter 113 at "e-inquiry" on VehicleServicePros.com





ACDelco Li-Ion 20V Brushless 1/2" Impact Wrench, No. ARI20156 Enter 114 at "e-inquiry" on VehicleServicePros.com

### Cornwell

bluePOWER 3/8" Sealed Head Ratchet, No. CAT7500BP

Enter 115 at "e-inquiry" on VehicleServicePros.com



#### **Michigan Pneumatic Tool**

1/2" Stubby Impact Wrench, No. MP-7775 Enter 116 at "e-inquiry" on VehicleServicePros.com

#### **Snap-on Tools**

14.4V Right Angle Cordless Screwdriver, No. CTSR761 Enter 117 at "e-inquiry" on VehicleServicePros.com



# GRANK UP CFN WITHOUT HIGH INSTALL COSTS.

#### LARGE, LOW-RPM PUMPS & MOTORS

### FLEXZILLA® GIVES YOU 10 HP PERFORMANCE ON SINGLE-PHASE POWER.

Give your shop the extra CFM performance it needs without an expensive three-phase electrical installation. The Flexzilla Pro is the only 10 HP two-stage air compressor with a simple, single-phase connection – delivering up to 39 CFM. You'll save money as well as your hearing thanks to Quiet Technology™ with Silencer™ noise suppression.

### Hear the difference for yourself at flexzilla.com/quiet.

SILENCER™ NOISE SUPPRESSION Patent Pending







#### PREMIUM HOSES, TOOLS & EQUIPMENT

The color CHARTREUSE as applied to the air compressor and gloves is a trademark owned by Weems Industries, Inc. © 2018 Legacy Manufacturing Company, All Rights Reserved.

Enter 118 at "e-inquiry" on VehicleServicePros.com









711397~

21



DRIVE CONTROL®

M12 FUEL<sup>™</sup> is engineered for the most demanding tradesmen in the world. M12 FUEL<sup>™</sup> delivers unrivaled performance in a compact structure and features three MILWAUKEE<sup>®</sup> exclusive innovations — the POWERSTATE<sup>™</sup> Brushless Motor, REDLITHIUM<sup>™</sup> Battery Pack and REDLINK PLUS<sup>™</sup> Intelligence Hardware and Software — that deliver unmatched power, run-time and durability.

Enter 119 at "e-inquiry" on VehicleServicePros.com

